

SGC

● D Type (Standard)

Item	Unit	60/10D	80/10D	80/20D	100/20D	100/30D	120/10D	120/20D	120/30D	120/40D
Max. Operation Pressure	MPa	0.50								
Inner Capacity	m ³	0.28	0.61	1.09	1.73	2.49	1.46	2.54	3.63	4.71
Consumption Electricity	kW	3.2/3.5 (50Hz/60Hz)	5.3	7.1	7.1	10.2	7.1	10.2	13.7	21.2
Used Steam Amount	kg/ Batch	16	32	61	91	133	73	139	207	274
Required Boiler capacity	kg/h	150	300	500	1,000	1,500	750	1,500	2,000	2,500
Compressor	kW	3.7	5.5	2.2	3.7	3.7	3.7	3.7	5.5	7.5
Air Tank	m ³	—	—	1	1	1	1	1	2	2
Number of Trolley	set	1	1	2	2	3	1	2	3	4
Tray Size	W·L·H (mm)	420×740×340	490×940×490		620×940×640		820×940×800			
Number of Tray loaded / Trolley	pce	12	18		23		29			
Number of processable Pouch / Trolley	pce	144	270		483		870			
Number of processable Pouch / Batch	pce	144	270	540	966	1,449	870	1,740	2,610	3,480

* Pouch Size : 130×170×20mm